



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM	NC	NC	NC	1E	1D	1C	DP1	2E	2D	2C	DP2	3E	3D	3C	DP3	4E	4D	4C	4B
PIN	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM	4A	4F	4G	3B	3A	3F	3G	COL	2B	2A	2F	2G	NC	1B	1A	1F	1G	NC	NC	COM

DISPLAY MODE:	POSITIVE & TN	DRIVE METHOD:	STATIC
FRONT POLARIZER:	TRANSMISSIVE	OPERATION TEMPERATURE:	-30°C TO 80°C
BACK POLARIZER:	TRANSFLECTIVE	STORAGE TEMPERATURE:	-35°C TO 85°C
VIEWING ANGLE:	6:00	CONNECTOR :	PIN
DRIVE VOLTAGE:	5V	ALL DIMENSION ARE IN mm WITH ±0.2 TOLERANCE UNLESS OTHERWISE SPECIFIED	

设计:

审核:

复查:

批准:

SCALE	TITLE	LCD DRAWING
UNIT: mm	PROJECT	HD6594
REV. 1	PAGE	1 OF 1
DATE	DATE	2002-11-21

HAINAN QINGHUA LCD TECHNOLOGY LTD