

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-	

VDD : 5.0V±5%  
 DISPLAY TYPE : STN BLUE, NEGATIVE MODE  
 POLARIZER MODE : TRANSMISSIVE  
 CONNECTOR : ZEBRA  
 VIEW ANGLE : 6 O'CLOCK  
 DRIVING METHOD : 4.5V, 1/16 DUTY, 1/5BIAS  
 DISPLAY DRIVER : KS0066 OR EQUIVALENT  
 BACKLIGHT COLOR : WHITE  
 BACKLIGHT Vf : 3.4V (TYP)  
 BACKLIGHT If : 20mA (TYP)  
 BEZEL FINISH : BLACK ELECTRO PLATING  
 OPERATING TEMP : 0°C TO +50°C  
 STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2005-04-18


CHECKED BY :

Approve By :



HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UC162C-BN-MB-N-LG-W



UNITS MM

TITLE CUSTOMER LCD

REV: A1 SHEET: 1 OF 1

SIZE: A4 SCALE: NTS