



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

VDD : 5.0V±5%
 DISPLAY TYPE : STN YG, POSITIVE MODE
 POLARIZER MODE : TRANSFLECTIVE
 CONNECTOR : ZEBRA
 VIEW ANGLE : 6 O'CLOCK
 DRIVING METHOD : 4.5V, 1/16 DUTY, 1/5BIAS
 DISPLAY DRIVER : KS0066 OR EQUIVALENT
 BACKLIGHT COLOR : YELLOW GREEN
 BACKLIGHT Vf : 2.1V (TYP)
 BACKLIGHT If : 20mA (TYP)
 BEZEL FINISH : BLACK ELECTRO PLATING
 OPERATING TEMP : -30°C TO +80°C
 STORAGE TEMP : -35°C TO +85°C

DRAWN BY : F T T 2005-04-18

CHECKED BY :

Approve By :

海南清华显示器科技开发有限公司
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UC162F-YP-FB-W-LG-YG

REV: A1
 SIZE: A4

SHEET: 1 OF 1
 SCALE: NTS

UNITS: MM
 TITL: CUSTOMER LCD