


11.0(14.0) MAX.
() FOR BACKLIGHT
5.0(8.5) MAX.



SCALE 6:1

| | | | | | | | | | | | | | | | |
|-----|-----|----|----|-----|---|-----|-----|-----|-----|-----|-----|-----|-----|------|------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
| VSS | VDD | VO | RS | R/W | E | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | LED+ | LED- |

VDD : 5.0V±5%
 DISPLAY TYPE : STN YG, POSITIVE MODE
 POLARIZER MODE : REFLECTIVE
 CONNECTOR : ZEBRA
 VIEW ANGLE : 6 O'CLOCK
 DRIVING METHOD : 4.5V, 1/16 DUTY, 1/5BIAS
 DISPLAY DRIVER : KS0066 OR EQUIVALENT
 BACKLIGHT COLOR : NA
 BACKLIGHT Vf : NA
 BACKLIGHT If : NA
 BEZEL FINISH : BLACK ELECTRO PLATING
 OPERATING TEMP : 0°C TO +50°C
 STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2005-04-18
 CHECKED BY :
 Approve By :

海南清华显示器科技开发有限公司
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

| | |
|-------|---------------|
| UNITS | MM |
| | CUSTOMER LCD |
| TITL | SHEET: 1 OF 1 |
| SCALE | SIZE: A4 |
| | SCALE: NTS |

UC204A-YP-RB-N