



1	2	3	4	5	6	7	8	9	10
VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3
11	12	13	14	15	16	17	18	19	20
DB4	DB5	DB6	DB7	CS1	CS2	RSTB	VOUT	LED+	LED-

VDD : 5.0V±5%
 DISPLAY TYPE : STN BLUE, NEGATIVE MODE
 POLARIZER MODE : TRANSMISSIVE
 CONNECTOR : ZEBRA
 VIEW ANGLE : 6 O'CLOCK
 DRIVING METHOD : 8.5V, 1/64 DUTY, 1/9BIAS
 DISPLAY DRIVER : KS0107 OR EQUIVALENT
 BACKLIGHT COLOR : WHITE
 BACKLIGHT Vf : 3.2V (TYP)
 BACKLIGHT If : 60mA (TYP)
 BEZEL FINISH : BLACK ELECTRO PLATING
 OPERATING TEMP : 0°C TO +50°C
 STORAGE TEMP : -10°C TO +60°C

DRAWN BY : F T T 2011-03-06
 CHECKED BY :
 Approve By :

海南清华显示器科技开发有限公司
 HAINAN QINGHUA LCD TECHNOLOGY DEVELOPMENT CO.,LTD

UNITS	MM
TITL	CUSTOMER LCD
SHEET: 1 OF 1	
SCALE: NTS	

UG64128A1-BN-MB-N-LG-W

REV: A1

SIZE: A4